

(19) World Intellectual Property Organization
International Bureau



(43) International Publication Date
26 July 2001 (26.07.2001)

PCT

(10) International Publication Number
WO 01/53779 A1

(51) International Patent Classification⁷: **G01D 5/347, B62D 15/02**

(21) International Application Number: **PCT/US01/01689**

(22) International Filing Date: **18 January 2001 (18.01.2001)**

(25) Filing Language: **English**

(26) Publication Language: **English**

(30) Priority Data:
60/177,023 19 January 2000 (19.01.2000) US

(71) Applicant (for all designated States except US): **HOLLAND NEWAY INTERNATIONAL, INC. [US/US]; 1950 Industrial Boulevard, P.O. Box 425, Muskegon, MI 49443-0425 (US).**

(72) Inventor; and

(75) Inventor/Applicant (for US only): **GALAZIN, Gregory, T. [US/US]; 5055 Anderson Road, Muskegon, MI 49445 (US).**

(74) Agent: **McGARRY, John, E.; Rader, Fishman, Grauer & McGarry, An Office of Rader, Fishman and Grauer PLLC, Suite 600, 171 Monroe Avenue, NW, Grand Rapids, MI 49503 (US).**


(81) Designated States (national): **AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CR, CU, CZ, DE, DK, DM, DZ, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, SL, TJ, TM, TR, TT, TZ, UA, UG, US, UZ, VN, YU, ZA, ZW.**

(84) Designated States (regional): **ARIPO patent (GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE, TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GW, ML, MR, NE, SN, TD, TG).**

Published:
— with international search report

[Continued on next page]

(54) Title: **SPRING BEAM SUSPENSION WITH COMPRESSED AXLE MOUNTING**



(57) Abstract: A suspension (10) adapted to mount on a vehicle frame having a pair of spaced frame rails (14). The suspension (10) comprises a pair of trailing arm assemblies (12) that carry an axle (16). Each trailing arm assembly comprises a frame bracket (24) adapted to be mounted to one of the frame rails (14) and a spring beam (20) pivotally mounted at one end to the frame bracket (24) for pivotal movement about a pivot axis (23) and adapted to carry an axle (16) at another end. A spring (26) is disposed between the spring beam other end and the corresponding frame rail to resist the rotational movement of the trailing arm toward the frame. An axle seat (62) is integrally formed in the spring beam (20) for mounting the axle (16) thereto. The spring beam (20) has a pivot axis center line and the axle seat has a center line, which is located outboard of the pivot axis center line.

WO 01/53779 A1



— *before the expiration of the time limit for amending the claims and to be republished in the event of receipt of amendments*

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.